T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Black Soft Elastic Rubber on Aluminium Plate Fixed Castor 200mm 380kg Load

Product code: BZKF200SRERBJ

Fabricated fixed castor with a top plate fixing fitted with a ergonomic black high elastic natural 55 shore A round profile rubberr tyred aluminium centred wheel with ball bearings. Wheel diameter 200mm, tread width 50mm, overall height 205mm, top plate 150mm x 110mm, hole centres 105mm x 80mm or 121mm x 59mm. Load capacity 380kg at 4kph and 152kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC ** FOR INTERNAL AND EXTERNAL TOWING USE **

Diameter (mm)	200
Fixing Option	Plate
Castor Type	Fixed
Bearing Type	Ball
Height (mm)	250
Plate Size (mm)	150 x 110
Hole Centres (mm)	105/121 x 80/59
To Suit Fixing Bolt (mm)	12
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	7.5
Fork Thickness (mm)	6
Load Capacity (kg)	380
Tread (mm)	50