T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Black Soft Elastic Speed Rubber on Aluminium Plate Swivel Castor 150mm 250kg Load

Product code: BZXP150SRERBJ

Pressed steel swivel castor with a flat plate fixing fitted with a black ergonomic high elastic natural 55 shore A round profile rubber tyre on aluminium centred wheel with ball bearings. Wheel diameter 150mm, tread width 47mm, overall height 200mm, plate size 135mm x 110mm, hole centres 105mm x 80mm. Load capacity 250kg at 4kph 100kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC. ** FOR INTERNAL TOWING ONLY **

Diameter (mm)	150
Castor Type	Swivel
Fixing Option	Plate
Height (mm)	200
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Ergonomic Rubber on Aluminium Rim / 55 Shore A
Temperature Resistance	-30 °C TO +80 °C
Bearing Type	Ball
Load Capacity (kg)	250
Tread (mm)	47
Swivel Radius (mm)	140
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 75/80
Top Plate Thickness (mm)	6
Fork Thickness (mm)	5
To Suit Fixing Bolt (mm)	10