T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Black Soft Elastic Speed Rubber on Aluminium Plate Swivel Castor 150mm 250kg Load

**Product code: BZSPH150SRERBJ**

Pressed steel swivel castor with a top plate fixing fitted with a black high elastic natural 55 shore A round profile rubber tyre wheel aluminium centre with ball bearings. Wheel diameter 150mm, tread width 47mm, overall height 190mm, top plate 135mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 250kg at 4kph and 100kph at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC ** FOR INTERNAL TOWING ONLY **

| | |
|---|---|
| Diameter (mm) | 150 |
| Castor Type | Swivel |
| Fixing Option | Plate |
| Height (mm) | 190 |
| Wheel Material | Rubber on Aluminium |
| Colour / Shore Hardness | Black Ergonomic Rubber on Aluminium Rim / 55 Shore A |
| Temperature Resistance | -30 °C TO +80 °C |
| Bearing Type | Ball |
| Load Capacity (kg) | 250 |
| Tread (mm) | 47 |
| Swivel Radius (mm) | 128 |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 80/75 |
| Top Plate Thickness (mm) | 5 |
| Fork Thickness (mm) | 5 |
| To Suit Fixing Bolt (mm) | 10 |