T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Black Soft Elastic Speed Rubber on Aluminium Plate Swivel Castor Brake 160mm 300kg Load

Product code: BZXP160SRERBJSWBLP

Pressed steel swivel castor with a flat plate fixing fitted with a black ergonomic high elastic natural 55 shore A round profile rubber tyre on aluminium centred wheel with ball bearings and total lock brake. Wheel diameter 160mm, tread width 50mm, overall height 205mm, plate size 162mm x 140mm, hole centres 140mm x 105mm. Load capacity 300kg at 4kph 120kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC ** FOR INTERNAL TOWING ONLY **

Diameter (mm)	160
Castor Type	Swivel with Total Lock Brake
Fixing Option	Plate
Height (mm)	205
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Ergonomic Rubber on Aluminium Rim / 55 Shore A
Temperature Resistance	-30 °C TO +80 °C
Bearing Type	Ball
Load Capacity (kg)	300
Tread (mm)	50
Swivel Radius (mm)	180
Plate Size (mm)	162 X 140
Hole Centres (mm)	140 X 105
Top Plate Thickness (mm)	6
Fork Thickness (mm)	5
To Suit Fixing Bolt (mm)	10