T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Elastic Rubber Cast Iron Plate Swivel Castor Brake 250mm 800kg Load

Product code: BZQ250CUBJSWB

Fabricated swivel castor with a flat plate fixing fitted with a 65 shore A black elastic rubber tyred cast iron centred wheel with ball bearing and total lock brake, Wheel diameter 250mm, tread width 75mm, overall height 314mm, plate size 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 800kg at 4kph and 280kg at 20kph. ** FOR INTERNAL AND EXTERNAL TOWING USE**

Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	314
Plate Size (mm)	170 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Cast Iron
Colour / Shore Hardness	Black Elastic Rubber on Cast Iron Rim / 65 Shore A
Temperature Resistance	-20 °C TO +60 °C
Top Plate Thickness (mm)	12
Fork Thickness (mm)	10
Swivel Radius (mm)	210
Load Capacity (kg)	800
Tread (mm)	75