T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Elastic Rubber on Aluminium Plate Bolt Hole Swivel Castor Brake 150mm 250kg Load

**Product code: BZMM150SRERBJBH16SWB**

Pressed steel swivel castor with a 16mm bolt hole fitted with a black ergonomic high elastic natural 55 shore A round profile rubber tyre on aluminium centred wheel with ball bearings and total lock brake. Wheel diameter 150mm, tread width 47mm, overall height 188mm, Load capacity 250kg. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC, also available with flat tread details on request

| | |
|---|---|
| Diameter (mm) | 150 |
| Castor Type | Swivel with Total Lock Brake |
| Fixing Option | Bolt Hole |
| Height (mm) | 188 |
| Wheel Material | Rubber on Aluminium |
| Colour / Shore Hardness | Black Ergonomic Rubber on Aluminium Rim / 55 Shore A |
| Temperature Resistance | -30 °C TO +80 °C |
| Bearing Type | Ball |
| Load Capacity (kg) | 250 |
| Tread (mm) | 47 |
| Swivel Radius (mm) | 168 |
| Head Dia (mm) | 114 |
| Fork Thickness (mm) | 4 |
| To Suit Fixing Bolt (mm) | 16 |