T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Elastic Speed Rubber on Cast Iron Plate Swivel Castor Brake 150mm 400kg Load

Product code: BZXP150CUBJSWBLP

Pressed steel swivel castor with a top plate fixing fitted with a 65 shore A black high elastic rubber on cast iron wheel with ball bearings and total lock brake. Wheel diameter 150mm, tread width 50mm, overall height 200mm, top plate 175mm x 140mm, hole centres 140mm x 1055mm; Load capacity 400kg at 4kph, 160kg at 10kph, 150kg at 16kph, 140kg at 20kph ** FOR INTERNAL TOWING USE ONLY **

Diameter (mm)	150
Castor Type	Swivel with Total Lock Brake
Fixing Option	Plate
Height (mm)	200
Wheel Material	Rubber on Cast Iron
Colour / Shore Hardness	Black Elastic Rubber on Cast Iron Rim / 65 Shore A
Temperature Resistance	-20 °C TO +60 °C
Bearing Type	Ball
Load Capacity (kg)	400
Tread (mm)	50
Swivel Radius (mm)	180
Plate Size (mm)	162 X 140
Hole Centres (mm)	140 X 105
Top Plate Thickness (mm)	6
Fork Thickness (mm)	5
To Suit Fixing Bolt (mm)	10