T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Elastic Speed Rubber Plate Swivel Braked Castor 406mm 1900kg Load

Product code: 2BZSAB400MKCUBJDBR

POA Fabricated zinc plated twin wheel swivel braked castor with plate fixing fitted with 2x black elastic rubber tyred on a steel disc centred wheel with ball bearings. Wheel diameter 406mm, tread width 2 x 104mm, overall height 484mm, plate size 175mm x 140mm, hole centre's 140mm x 105mm. Load capacity 1900kg at 4kph, 1040kg at 10kph and 860kg at 16kph
MANUFACTURED TO ORDER

Diameter (mm)	400
Fixing Option	Plate
Castor Type	Swivel with Wheel Brake
Bearing Type	Ball
Plate Size (mm)	175 X 140
Hole Centres (mm)	140 X 105
Height (mm)	484
Swivel Radius (mm)	278
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Steel
Colour / Shore Hardness	Black Elastic Rubber on Steel Rim / 65 Shore A
Temperature Resistance	"-20 °C TO +60 °C
Tread (mm)	2 x 104
Load Capacity (kg)	1900