T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Electrically Conductive Polyurethane Nylon Swivel Castor Brake Plate 125mm 150kg

**Product code: SSMM125PNBECSWB**

Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with a black electrically conductive polyurethane on nylon wheel with roller bearing and a total lock brake. Wheel diameter 125mm, tread width 35mm, overall height 155mm, top plate 105mm x 85mm, hole centres 80mm x 60mm. Load capacity 150kg Conductive ffers a resistance R<10000 Ohm.

| | |
|---|---|
| Diameter (mm) | 125 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Height (mm) | 155 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Black Polyurethane on Nylon Rim / 97 Shore A |
| Bearing Type | Roller |
| Tread (mm) | 35 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 8 |
| Load Capacity (kg) | 150 |
| Temperature Resistance | -20 °C TO +80 °C |
| Plate Size (mm) | 105 X 85 |
| Hole Centres (mm) | 80 X 60 |
| Top Plate Thickness (mm) | 2 |
| Swivel Radius (mm) | 123 |