T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Electrically Conductive Rubber Plate Swivel Castor 150mm 100kg Load

**Product code: BZM150GREC**

Pressed steel swivel castor with a top plate fitted with a grey electrically conductive rubber on grey polypropylene centred wheel, Wheel diameter 150mm, 32mm tread width, 181mm overall height, 90mm x 70mm top plate, 75mm x 56mm or 64mm x 44mm bolt holes, with a load capacity of 100kgs. Conductive offers a resistance R<10__ **Manufactured to Order**

| | |
|---|---|
| Diameter (mm) | 150 |
| Fixing Option | Plate |
| Castor Type | Swivel |
| Plate Size (mm) | 90 x 70 |
| Hole Centres (mm) | 64/75 x 44/56 |
| Height (mm) | 181 |
| Bearing Type | Plain |
| Swivel Radius (mm) | 120 |
| Wheel Material | Electrically Conductive Rubber |
| Colour / Shore Hardness | Grey Electrically Conductive Rubber on Nylon Rim / 85 Shore A |
| Top Plate Thickness (mm) | 2 |
| Fork Thickness (mm) | 2 |
| Temperature Resistance | -15 °C TO +80 °C |
| To Suit Fixing Bolt (mm) | 8 |
| Tread (mm) | 32 |
| Load Capacity (kg) | 100 |