T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Electrically Conductive Rubber Plate Swivel Castor 50mm 50kg Load

Product code: SSRA50GREC

Grade 304 Pressed stainless steel swivel castor with a flate plate fitted with a grey electrically conductive rubber tyre on polypropylene centred wheel with a plain bore. Wheel diameter 50mm, tread width 24mm, overall height 74mm. plate size 60mm x 60mm, hole centres 49.5mm x 49.5mm or 42.5m,m x 42.5mm Load capacity 50kg.Conductive offers a resistance R<10__

Diameter (mm)	50
Fixing Option	Plate
Castor Type	Swivel
Height (mm)	74
Wheel Material	Rubber on Polypropylene
Colour / Shore Hardness	Grey Rubber on Polypropylene Rim / 85 Shore A
Bearing Type	Plain
Tread (mm)	24
Fork Thickness (mm)	1.8
To Suit Fixing Bolt (mm)	6
Load Capacity (kg)	50
Temperature Resistance	-15 °C TO +80 °C
Plate Size (mm)	60 x 60
Hole Centres (mm)	49/43 x 49/43
Top Plate Thickness (mm)	1.8
Swivel Radius (mm)	50