T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Electrically Conductive Rubber Plate Swivel Castor 75mm 60kg Load

**Product code: SSRA75GREC**

Grade 304 Pressed stainless steel swivel castor with a flat plate fitted with a grey electrically conductive rubber tyre on polypropylene centred wheel with a plain bore. Wheel diameter 75mm, tread width 24mm, overall height 101mm. plate size 60mm x 60mm, hole centres 49.5mm x 49.5mm or 42.5m,m x 42.5mm Load capacity 60kg.Conductive offers a resistance R<10__

| | |
|---|---|
| Diameter (mm) | 75 |
| Fixing Option | Plate |
| Castor Type | Swivel |
| Height (mm) | 101 |
| Wheel Material | Rubber on Polypropylene |
| Colour / Shore Hardness | Grey Rubber on Polypropylene Rim / 85 Shore A |
| Bearing Type | Plain |
| Tread (mm) | 24 |
| Fork Thickness (mm) | 1.8 |
| To Suit Fixing Bolt (mm) | 6 |
| Load Capacity (kg) | 70 |
| Temperature Resistance | -15 °C TO +80 °C |
| Plate Size (mm) | 60 x 60 |
| Hole Centres (mm) | 49/43 x 49/43 |
| Top Plate Thickness (mm) | 1.8 |
| Swivel Radius (mm) | 68 |