T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Polyurethane Cast Iron Plate Swivel Castor 200mm 1600kg Load

Product code: JAZHD200PTBJ

Side plate fixing fabricated zinc plated jacking unit fitted with a 200mm swivel castor with a polyurethane on cast iron centred ball bearing wheel, Tread width 75mm plate size 200mm x 110mm, hole centres 135mm x 80mm, height 681mm/831mm, maximum lift is 150mm. Load capacity 1600kg. Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. When jacked up to the height please beware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. DO NOT OVERWIND Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit)

Diameter (mm)	200
Castor Height (mm)	264
Castor Type	Swivel
Swivel Radius (mm)	165
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	16
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / 94 Shore A
Temperature Resistance	-20 °C TO +80 °C
Load Capacity (kg)	1600
Tread (mm)	75
Height (mm)	681 / 831
Lifting Stroke (mm)	150
Handle Option	Fixed