T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Polyurethane Cast Iron Plate Swivel Castor Brake 150mm 500kg Load

**Product code: BZPH150PTBJSWB**

Pressed steel swivel castor with a top plate fixing fitted with a polyurethane tyre on cast iron centred wheel with ball bearings and total lock brake. Wheel diameter 150mm, tread width 50mm, overall height 190mm, top plate 135mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 500kg.

| | |
|---|---|
| Diameter (mm) | 150 |
| Castor Type | Swivel with Total Lock Brake |
| Fixing Option | Plate |
| Height (mm) | 190 |
| Wheel Material | Polyurethane on Cast Iron |
| Colour / Shore Hardness | Brown Polyurethane on Cast Iron Rim / 94 Shore A |
| Temperature Resistance | -20 °C TO +80 °C |
| Bearing Type | Ball |
| Load Capacity (kg) | 500 |
| Tread (mm) | 50 |
| Swivel Radius (mm) | 167 |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 80/75 |
| Top Plate Thickness (mm) | 4 |
| Fork Thickness (mm) | 4 |
| To Suit Fixing Bolt (mm) | 10 |