T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Polyurethane Nylon Plate Swivel Castor 100mm 250kg Load

**Product code: SSPH100NPB**

Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with a red polyurethane tyred white nylon centred wheel with a roller bearing. Wheel diameter 100mm, tread width 34mm, overall height 132mm, top plate 135mm x 110mm, hole centres 105mm x 80mm. Load capacity 250kg

| | |
|---|---|
| Diameter (mm) | 100 |
| Fixing Option | Plate |
| Castor Type | Swivel |
| Height (mm) | 132 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Red Polyurethane on Nylon Rim / 96 Shore A |
| Bearing Type | Roller |
| Tread (mm) | 33 |
| Fork Thickness (mm) | 4 |
| To Suit Fixing Bolt (mm) | 10 |
| Load Capacity (kg) | 250 |
| Temperature Resistance | -20 °C TO +70 °C |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 80/75 |
| Top Plate Thickness (mm) | 4 |
| Swivel Radius (mm) | 90 |