T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Polyurethane Nylon Plate Swivel Castor Brake 100mm 250kg Load

**Product code: BZPH100NPBSWB**

Pressed steel swivel castor with a top plate fixing fitted with a red polyurethane tyre on white nylon centred wheel with a roller bearing and a total lock brake. Wheel diameter 100mm, tread width 34mm, overall height 132mm, plate size 135mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 250kg.

| | |
|---|---|
| Diameter (mm) | 100 |
| Castor Type | Swivel with Total Lock Brake |
| Fixing Option | Plate |
| Height (mm) | 132 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Red Polyurethane on Nylon Rim / 96 Shore A |
| Temperature Resistance | -20 °C TO +70 °C |
| Bearing Type | Roller |
| Load Capacity (kg) | 250 |
| Tread (mm) | 34 |
| Swivel Radius (mm) | 120 |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 80/75 |
| Top Plate Thickness (mm) | 4 |
| Fork Thickness (mm) | 4 |
| To Suit Fixing Bolt (mm) | 10 |