T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Polyurethane Nylon Plate Swivel Castor Brake Locking Castor 100mm 200kg Load

Product code: JAB100NPSWB

Open screw thread jacking castor with side fitting nuts with 160mm lift fitted with a 100mm white zinc plated swivel pressed steel castor with a red polyurethane tyred white nylon centred wheel with plain bore and total lock brake. with a load capacity of 200kg Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units.1 extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in bending the thread but more likely the castor will tear away from the screw thread. Please refer to the BIL catalogue or request a drawing

Diameter (mm)	100
Castor Height (mm)	128
Castor Type	Swivel with Total Lock Brake
Swivel Radius (mm)	120
Fixing Option	Plate
Bearing Type	Plain
To Suit Fixing Bolt (mm)	12
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Red Polyurethane on Nylon Rim / 96 Shore A
Temperature Resistance	-20 °C TO +70 °C
Load Capacity (kg)	200
Tread (mm)	33
Height (mm)	438
Lifting Stroke (mm)	160