T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Polyurethane Nylon Plate Swivel Castor Brake Locking Castor 125mm 350kg Load

## Product code: JAZHS125NPBJSWB

Side winding jacking unit with maximum lift of 200mm fitted with a Fabricated swivel castor with a top plate fixing fitted with a red polyurethane tyre on a white nylon centred wheel with ball bearings. Wheel diameter 125mm, tread width 40mm,maximum Load for the complete unit is capacity 350kg. Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. for other dimensions please refer to the BIL catalogue or request a drawing. When jacked up to the height please beware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. please note BIL do not recommend brakes on jacking castors. DO NOT OVERWIND Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit)

| | |
|---|---|
| Diameter (mm) | 125 |
| Castor Height (mm) | 165 |
| Castor Type | Swivel with Total Lock Brake |
| Swivel Radius (mm) | 101 |
| Fixing Option | Plate |
| Bearing Type | Ball |
| To Suit Fixing Bolt (mm) | 10 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Red Polyurethane on Nylon Rim / 96 Shore A |
| Temperature Resistance | -20 °C TO +70 °C |
| Load Capacity (kg) | 350 |
| Tread (mm) | 40 |
| Height (mm) | 572 / 772 |
| Lifting Stroke (mm) | 200 |
| Handle Option | Fixed |