T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Puncture Proof Polyurethane Plate Swivel Castor Brake 260mm 100kg Load

**Product code: BZPC260MPUBDSWB/LITE**

Pressed steel swivel castor with a top plate fixing fitted wth a black diamond pattern pucture proof tyre on a pressed steel centre with roller bearings and total lock brake. Wheel diameter 260mm, tread width 85mm, overall height 302mm, top plate 200mm x 160mm, hole centres 150mm x 115mm. Load capacity 100kg.

| | |
|---|---|
| Diameter (mm) | 260 |
| Castor Type | Swivel with Total Lock Brake |
| Fixing Option | Plate |
| Plate Size (mm) | 200 X 160 |
| Height (mm) | 307 |
| Hole Centres (mm) | 150 x 115 |
| Swivel Radius (mm) | 215 |
| Tread (mm) | 85 |
| Temperature Resistance | -10 °C TO +60 °C |
| To Suit Fixing Bolt (mm) | 14 |
| Bearing Type | Roller |
| Wheel Material | Puncture Proof Wheels |
| Load Capacity (kg) | 100 |
| Colour / Shore Hardness | Black Puncture Proof Tyre on Steel Rims / Low PU |
| Top Plate Thickness (mm) | 4 |
| Fork Thickness (mm) | 3 |