T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Red Polyurethane Nylon Fixed Plate Castor 200mm 700kg Load

**Product code: SSPHF200NPB/HD**

Grade 304 Pressed stainless steel fixed castor with a top plate fixing fitted with a red polyurethane tyred white nylon centred wheel with a roller bearing. Wheel diameter 200mm, tread width 48mm, overall height 238mm, top plate 135mm x 110mm, hole centres 105mm x 80mm. Load capacity 700kg

| | |
|---|---|
| Diameter (mm) | 200 |
| Fixing Option | Plate |
| Castor Type | Fixed |
| Height (mm) | 238 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Red Polyurethane on Nylon Rim / 96 Shore A |
| Bearing Type | Roller |
| Tread (mm) | 50 |
| Fork Thickness (mm) | 4 |
| To Suit Fixing Bolt (mm) | 10 |
| Load Capacity (kg) | 700 |
| Temperature Resistance | -20 °C TO +70 °C |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 80/75 |
| Top Plate Thickness (mm) | 4 |