T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Soft Ergonomic Speed Polyurethane Plate Swivel Castor Brake 150mm 500kg Load

**Product code: BZXP150RSPABJSWB**

Pressed steel swivel castor with a top plate fixing fitted with a 75 shore A Blue Ergonomic polyurethane tyre on aluminium centred wheel with ball bearings with total lock brake. Wheel diameter 150mm, tread width 50mm, overall height 200mm, top plate 135mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 500kg at 4kph and 200kg at 16kph **FOR INTERNAL TOWING ONLY**

| | |
|---|---|
| Diameter (mm) | 150 |
| Height (mm) | 200 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Swivel Radius (mm) | 180 |
| Bearing Type | Ball |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 75/80 |
| Wheel Material | Polyurethane on Aluminium |
| Colour / Shore Hardness | Blue Ergonomic Polyurethane on Aluminium Rim / 75 Shore A |
| Tread (mm) | 50 |
| Load Capacity (kg) | 500 |
| Top Plate Thickness (mm) | 6 |
| Fork Thickness (mm) | 5 |
| To Suit Fixing Bolt (mm) | 10 |
| Temperature Resistance | -20 °C TO +70 °C |