T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Soft Speed Polyurethane Plate Swivel Castor 200mm 700kg Load

Product code: BZXP200SPABJ

Pressed steel swivel castor with a top plate fixing fitted with a blue 75 shore A polyurethane tyre on aluminium centred wheel with ball bearings. Wheel diameter 200mm, tread width 50mm, overall height 245mm, top plate 135mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 700kg at 4kph and 280kg at 16kph **FOR INTERNAL TOWING ONLY**

Diameter (mm)	200
Load Capacity (kg)	700
Bearing Type	Ball
Fixing Option	Plate
Castor Type	Swivel
To Suit Fixing Bolt (mm)	10
Swivel Radius (mm)	165
Height (mm)	245
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 75/80
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Blue Polyurethane on Aluminium Rim / 75 Shore A
Tread (mm)	50
Top Plate Thickness (mm)	6
Temperature Resistance	-20 °C TO +70 °C
Fork Thickness (mm)	5