T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Softer Ergonomic Polyurethane Plate Fixed Castor 150mm 500kg Load

Product code: BZSABF150RSPABJ

Fabricated zinc plated fixed castor with plate fixing fitted with a blue 75 shore A polyurethane tyre aluminium centred wheel centred wheel with ball bearings. Wheel diameter 150mm, tread width 50mm, overall height 250mm, plate size 138mm x 110mm, hole centrtes 105mm x 80mm/75mm. Load capacity 500kg at 4kph and 200 at 16kph. ** FOR INTERNAL AND EXTERNAL TOWING USE**

Diameter (mm)	150
Fixing Option	Plate
Castor Type	Fixed
Bearing Type	Ball
Height (mm)	200
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80
To Suit Fixing Bolt (mm)	10
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Blue Ergonomic Polyurethane on Aluminium Rim / 75 Shore A
Temperature Resistance	-20 °C TO +70 °C
Top Plate Thickness (mm)	8
Fork Thickness (mm)	6
Load Capacity (kg)	500
Tread (mm)	50