T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Softer Ergonomic Polyurethane Plate Swivel Castor Brake 100mm 300kg Load

Product code: BZXP100RSPABJSWB

Pressed steel swivel castor with a top plate fixing fitted with a blue 75 shore A ergonomic polyurethane round profile wheel with aluminium centre with ball bearings and total lock brake. Wheel diameter 100mm, tread width 40mm, overall height 140mm, plate size 105 mm x 86mm, hole centres 80/77mm x 60mm Load capacity 300kg.

Diameter (mm)	100
Castor Type	Swivel with Total Lock Brake
Fixing Option	Plate
Height (mm)	140
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Blue Ergonomic Polyurethane on Aluminium Rim / 75 Shore A
Temperature Resistance	-20 °C TO +70 °C
Bearing Type	Ball
Load Capacity (kg)	300
Tread (mm)	40
Swivel Radius (mm)	135
Plate Size (mm)	105 x 86
Hole Centres (mm)	80 / 77 X 60
Top Plate Thickness (mm)	6
Fork Thickness (mm)	5
To Suit Fixing Bolt (mm)	8