T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Softer Ergonomic Polyurethane Plate Swivel Castor Brake 125mm 350kg Load

Product code: BZXP125RSPABJSWB

Pressed steel swivel castor with a top plate fixing fitted with a ergonomic blue polyurethane 75 shore A tyre on aluminium centre wheel with ball bearings and total lock brake. Wheel diameter 125mm, tread width 41mm, overall height 165mm, top plate 105mm x 86mm, hole centres 80mm x 60mm. Load capacity 350kg at 4kph.

Diameter (mm)	125
Castor Type	Swivel with Total Lock Brake
Fixing Option	Plate
Height (mm)	165
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Blue Ergonomic Polyurethane on Aluminium Rim / 75 Shore A
Temperature Resistance	-20 °C TO +70 °C
Bearing Type	Ball
Load Capacity (kg)	350
Tread (mm)	41
Swivel Radius (mm)	135
Plate Size (mm)	105 x 86
Hole Centres (mm)	80 / 77 X 60
Top Plate Thickness (mm)	6
Fork Thickness (mm)	5
To Suit Fixing Bolt (mm)	8