T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Vulkollan Polyurethane Cast Iron Plate Swivel Castor Brake 300mm 1900kg Load

Product code: BZQ300VPTBJSWB

POA Fabricated swivel castor with a flat plate fixing fitted with a High grade Vulkollan polyurethane tyre on cast iron centred wheel with a ball bearing and total lock brake. Wheel diameter 300mm, tread width 75mm, overall height 365mm, plate size 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 1900kg at 6kph max speed. **MANUFACTURED TO ORDER**

Diameter (mm)	300
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	365
Plate Size (mm)	170 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	14
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Vulkollan Polyurethane on Cast Iron / 92 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	12
Fork Thickness (mm)	10
Swivel Radius (mm)	232
Load Capacity (kg)	1900
Tread (mm)	75